



Zoll Leads Out Radiotransparent Reference: C100LOAC-ZOLL

1 Pair / Pouch 10 Pairs / Case

PRODUCT INFORMATION

 Pad Size
 4.7 x 6.1 in / 11.9 x 15.6 cm

 Product Surface Area
 28.8 in² / 185.5 cm²

 Adhesive Area
 28.8 in² / 185.5 cm²

 Conductive Area (2 Pads)
 32.2 in² / 207.6 cm²

 Gel Area
 16.6 in² / 107.1 cm²

 Pad Thickness
 0.09 in / 2.4 mm

 Lead Wire Length
 60 in / 1.5 m

MATERIALS

Substrate Material Polyethylene Foam Acrylic, Medical Grade **Adhesive Gel Characteristics** Conductive, Adhesive Hydrogel **Conductive Element** Carbon Bleached Kraft Paper **Release Liner Impedance Class** Iow Comparable to Zoll OEM **Adapter / Connector** PVC **Integrated Lead Wire Jacketing Integrated Lead Wire Cord** Carbon

ELECTRICAL PERFORMANCE (ANSI/AAMI EC 12)

Meets or Exceeds IEC 60601-2-4:2010

FEATURES

MR Compatible No X-ray Translucence Radiotransparent

REGULATORY STATUS

CE Marked Yes Tes



PACKAGING

 Product Weight
 3.2oz. / 90.7g

 Product Packaging Size (L x W)
 6.2 x 9.3 in

 15.7 x 23.5 cm

 Case Dimensions - Box (Size)
 10.8 x 6.8 x 6.5 in

 27.3 x 17.1 x 16.5 cm

 Leads Packaged
 Outside Package

BIOCOMPATIBILITY

ISO 10993 Passed Latex Free Yes

ENVIRONMENTAL

Halogenated Hydrocarbon Content (e.g. PVC)NonePhthalate Derivatives Content (e.g. DEHP)NoneRoHS CompliantYesREACH CompliantYes

SHELF LIFE

Product Shelf Life36 Months **Temperature Storage**Min -4; Max 104 °F / Min -20; Max +40 °C

Part Number: 6600023H