



# Zoll Radiolucent Reference: T100AC-ZOLL

1 Pair / Pouch 10 Pairs / Case

### **PRODUCT INFORMATION**

 Pad Size
 4.7 x 6.1 in / 11.9 x 15.6 cm

 Product Surface Area
 28.8 in² / 185.5 cm²

 Adhesive Area
 28.8 in² / 185.5 cm²

 Conductive Area (2 Pads)
 32.2 in² / 207.6 cm²

 Gel Area
 16.6 in² / 107.1 cm²

 Pad Thickness
 0.09 in / 2.4 mm

 Lead Wire Length
 60 in / 1.5 m

### **MATERIALS**

**Substrate Material** Polyethylene Foam Acrylic, Medical Grade **Adhesive Gel Characteristics** Conductive, Adhesive Hydrogel **Conductive Element** Tin Copper Bleached Kraft Paper **Release Liner Impedance Class Adapter / Connector** Comparable to Zoll OEM PVC **Integrated Lead Wire Jacketing Integrated Lead Wire Cord** Tin Copper

# ELECTRICAL PERFORMANCE (ANSI/AAMI EC 12)

Meets or Exceeds IEC 60601-2-4:2010

#### **FEATURES**

MR Compatible No X-ray Translucence Radiolucent

#### **REGULATORY STATUS**

CE Marked Yes Tes



#### **PACKAGING**

 Product Weight
 3.2oz. / 90.7g

 Product Packaging Size (L x W)
 6.2 x 9.3 in

 15.7 x 23.5 cm

 Case Dimensions - Box (Size)
 10.8 x 6.8 x 6.5 in

 27.3 x 17.1 x 16.5 cm

**Leads Packaged** 

#### **BIOCOMPATIBILITY**

ISO 10993 Passed Latex Free Yes

#### **ENVIRONMENTAL**

Halogenated Hydrocarbon Content (e.g. PVC)NonePhthalate Derivatives Content (e.g. DEHP)NoneRoHS CompliantYesREACH CompliantYes

## **SHELF LIFE**

**Product Shelf Life**36 Months **Temperature Storage**Min -4; Max 104 °F / Min -20; Max +40 °C

Part Number: 6600095H

Inside Package