



SimplySnap Offset

O-4227-5 - Disposable ECG Electrode - 5 Pack

Reference: **O-4227-5 OFFSET ELECTRODE**



5 Electrodes / Pouch
1000 Electrodes / Case

APPLICATION

General Patient Monitoring

For: 72 Hours

PRODUCT INFORMATION

Shape	Teardrop
Size (excl. grip)	1.65 * 1.06 in / 42 * 27 mm
Sensor (Eyelet) Diameter	0.0883502 in / 57 mm
Substrate Thickness (adapter excluded)	0.04 in / 1 mm
Total Product Surface Area	1.3237 in ² / 854 mm ²
Gel Area	0.351851 in ² / 227 mm ²
Adhesive Area	0.885052 in ² / 571 mm ²
Integrated Lead Wire (length / color)	N/A

MATERIALS

Substrate Material	Polyethylene Foam
Adhesive	Acrylic, Medical Grade
Gel Type	Conductive Wet Gel
Foam (Sponge) Material	Polyurethane Reticulated Foam
Release Liner	PET
Sensor Polymer	Ag/AgCl plated ABS
Adaptor / Connector (Stud)	Stainless Steel
Integrated Lead Wire Jacketing	N/A
Integrated Lead Wire Cord	N/A

ELECTRICAL PERFORMANCE (ANSI/AAMI EC 12)

ACZ impedance (before defib simulation) @10 Hz	2000 Ohm
DC Offset Voltage (before defib simulation)	100 mV
SDR Slope (remaining potential after defib) @ 30 Sec int.	1 mV/sec
ACZ impedance repeat (after defib simulation)	2000 Ohm
COIIN (combined offset instability and inner noise)	150 µV
Bias Current Tolerance (DC offset voltage after DC loading)	100 mV

FEATURES

MR Conditional	No
X-ray Translucence	No
Integrated Abrader	No
Repositionability	No

PACKAGING

Product Packaging Material	PE, Foil, PE
Resealable Pouch	Yes
Product Packaging Size (L x W)	8.46 x 3.54 in 21.5 x 9 cm
Department Packaging - Box (L x W)	18.5 x 8.86 x 9.06 in 47 x 22.5 x 23 cm
Transport Packaging - Carton (L x W)	18.9 x 18.11 x 27.9 in 48 x 46 x 71 cm

BIOCOMPATIBILITY

ISO 10993	Yes
Latex Free	Yes

ENVIRONMENTAL

Halogenated Hydrocarbon Content (e.g. PVC)	None
Phthalate Derivatives Content (e.g. DEHP)	None
RoHS Compliant	Yes
REACH Compliant	Yes

SHELF LIFE

Product Shelf Life (in accordance with storage guidelines)	24 Months
--	-----------

REGULATORY STATUS

CE Mark according to MDD 93/42/EEC CE marked

Reorder Part Number: 32029080