

## For: Hours

**Shape**  
**Size (excl. grip)**  
**Sensor (Eyelet) Diameter**  
**Substrate Thickness (adapter excluded)**  
**Total Product Surface Area**  
**Gel Area**  
**Adhesive Area**  
**Integrated Lead Wire (length / color)**

- Substrate Material**
- Adhesive**
- Gel Type**
- Foam (Sponge) Material**
- Release Liner**
- Sensor Polymer**
- Adaptor / Connector (Stud)**
- Integrated Lead Wire Jacketing**
- Integrated Lead Wire Cord**

<b>ACZ impedance</b> (before defib simulation) @ <b>10 Hz</b>	Ohm
<b>DC Offset Voltage</b> (before defib simulation)	mV
<b>SDR Slope</b> (remaining potential after defib) @ <b>30 Sec int.</b>	mV/sec
<b>ACZ impedance repeat</b> (after defib simulation)	Ohm
<b>COIIN</b> (combined offset instability and inner noise)	µV
<b>Bias Current Tolerance</b> (DC offset voltage after DC loading)	mV

**MR Conditional**  
**X-ray Translucence**  
**Integrated Abrader**  
**Repositionability**

**Product Packaging Material**  
**Resealable Pouch**  
**Product Packaging Size (L x W)**  
**Department Packaging - Box ( L x W)**  
**Transport Packaging - Carton (L x W)**

ISO 10993  
Latex Free

Halogenated Hydrocarbon Content (e.g. PVC)  
Phthalate Derivatives Content (e.g. DEHP)  
RoHS Compliant  
REACH Compliant

**Product Shelf Life** (in accordance with storage guidelines)**Reorder Part Number:**