



Electrodes / Pouch  
Electrodes / Case

## APPLICATION

For: Hours

## PRODUCT INFORMATION

Shape  
Size (excl. grip)  
Sensor (Eyelet) Diameter  
Substrate Thickness (adapter excluded)  
Total Product Surface Area  
Gel Area  
Adhesive Area  
Integrated Lead Wire (length / color)

## MATERIALS

Substrate Material  
Adhesive  
Gel Type  
Foam (Sponge) Material  
Release Liner  
Sensor Polymer  
Adaptor / Connector (Stud)  
Integrated Lead Wire Jacketing  
Integrated Lead Wire Cord

## ELECTRICAL PERFORMANCE (ANSI/AAMI EC 12)

|                                                                    |        |
|--------------------------------------------------------------------|--------|
| <b>ACZ impedance</b> (before defib simulation) @10 Hz              | Ohm    |
| <b>DC Offset Voltage</b> (before defib simulation)                 | mV     |
| <b>SDR Slope</b> (remaining potential after defib) @ 30 Sec int.   | mV/sec |
| <b>ACZ impedance repeat</b> (after defib simulation)               | Ohm    |
| <b>COIIN</b> (combined offset instability and inner noise)         | µV     |
| <b>Bias Current Tolerance</b> (DC offset voltage after DC loading) | mV     |

## FEATURES

MR Conditional  
X-ray Translucence  
Integrated Abrader  
Repositionability

## PACKAGING

|                                      |          |
|--------------------------------------|----------|
| Product Packaging Material           |          |
| Resealable Pouch                     |          |
| Product Packaging Size (L x W)       | in<br>cm |
| Department Packaging - Box (L x W)   | in<br>cm |
| Transport Packaging - Carton (L x W) | in<br>cm |

## BIOCOMPATIBILITY

ISO 10993  
Latex Free

## ENVIRONMENTAL

Halogenated Hydrocarbon Content (e.g. PVC)  
Phthalate Derivatives Content (e.g. DEHP)  
RoHS Compliant  
REACH Compliant

## SHELF LIFE

Product Shelf Life (in accordance with storage guidelines)

## REGULATORY STATUS

CE Mark according to MDD 93/42/EEC



Reorder Part Number: