



Solid Gel



Electrodes / Pouch
Electrodes / Case

APPLICATION

For: Hours

PRODUCT INFORMATION

Shape
Size (excl. grip)
Sensor (Eyelet) Diameter
Substrate Thickness (adapter excluded)
Total Product Surface Area
Gel Area
Adhesive Area
Integrated Lead Wire (length / color)

MATERIALS

Substrate Material
Adhesive
Gel Type
Foam (Sponge) Material
Release Liner
Sensor Polymer
Adaptor / Connector (Stud)
Integrated Lead Wire Jacketing
Integrated Lead Wire Cord

ELECTRICAL PERFORMANCE (ANSI/AAMI EC 12)

ACZ impedance (before defib simulation) @10 Hz	Ohm
DC Offset Voltage (before defib simulation)	mV
SDR Slope (remaining potential after defib) @ 30 Sec int.	mV/sec
ACZ impedance repeat (after defib simulation)	Ohm
COIIN (combined offset instability and inner noise)	µV
Bias Current Tolerance (DC offset voltage after DC loading)	mV

FEATURES

MR Conditional
X-ray Translucence
Integrated Abrader
Repositionability

PACKAGING

Product Packaging Material
Resealable Pouch
Product Packaging Size (L x W)
Department Packaging - Box (L x W)
Transport Packaging - Carton (L x W)

in
cm
in
cm
in
cm

BIOCOMPATIBILITY

ISO 10993
Latex Free

ENVIRONMENTAL

Halogenated Hydrocarbon Content (e.g. PVC)
Phthalate Derivatives Content (e.g. DEHP)
RoHS Compliant
REACH Compliant

SHELF LIFE

Product Shelf Life (in accordance with storage guidelines)

REGULATORY STATUS

CE Mark according to MDD 93/42/EEC



Reorder Part Number: